

## Rough Terrain Forklift

Used Rough Terrain Forklift Ontario Canada - Broadly defined, a forklift truck uses two forks to load, transport and unload material. Forklifts fall into two main categories, industrial forklifts and rough terrain forklifts. Industrial forklifts are mainly used in loading docks and warehouse applications with smooth and level surfaces. Rough terrain forklifts are better suited for rocky environments and uneven surfaces. Due to size, tires, and weight capacity, a rough terrain lift is primarily used outdoors, often at construction sites. The main difference between rough terrain and industrial forklifts is the cushion tires that are on industrial forklift models. Rough terrain forklifts, on the other hand, are fitted with pneumatic tires, a type of tractor tire allowing for better traction and flotation properties. Internal combustion engines can power industrial forklifts; however, more often they rely on an electrical source such as a fuel cell or better. Rough terrain models typically rely on an internal combustion engine. Types of Class 7 Rough Terrain Forklift Trucks

There are three main types of Class 7 Rough Terrain Forklift Trucks: 1. Straight mast forklifts; 2. Telehandler forklifts; and 3. Rotating telehandler forklifts. Regardless of its type, all rough terrain forklift trucks are designed to handle, as their name suggests, natural rough terrain and disturbed rough terrain typical of construction and military sites. The rough terrain models travel and perform well in difficult locations. Additional consideration needs to be given for rough terrain forklift options while raising loads in difficult conditions in order to stay safe from tipping over. The machine needs to remain in a stable position prior to lowering, lifting or moving any items. Rough terrain forklift operators must practice correct lifting techniques to remain stable on the ground. Straight Mast Forklifts Straight mast forklifts are designed to transport building materials around a range of rough terrain sites such as demolition and construction sites. Pneumatic cushion tires allow this forklift better maneuverability and accessibility around difficult terrain. Uneven ground and rough surfaces are no match for pneumatic tires. Most straight mast forklift units have 2WD or 4WD configurations. Even though these machines are better utilized in exterior locations, many straight mast forklifts operate with propane or diesel, enabling them to be used indoors for short timeframes. The lift capacities of straight mast forklifts are similar to most standard forklifts with a range of approximately 5,000 to 36,000 pounds. Telehandler or Telescopic Handler Forklifts Telehandler or telescopic handler forklift trucks are equipped with a telescoping boom, giving them their name. Telescoping booms are handy for allowing the machine to load and place items at different lift heights and distances in front of the forklift. Better reachability delivers greater flexibility to the forklift operator while placing loads. Featuring two wheels found at the front and two wheels at the rear, the standard telehandler is a long and low machine. The telescopic boom can be found at the back of the forklift, mounted on a pivot that is attached many feet higher than the frame of the unit. The hydraulic fluid tank and fuel tank are mounted on the opposite side of the cab which is usually situated on the left side of the forklift. The forklift engine and transmission are situated along the center of the machine. This popular design showcases a balanced forklift which is ideal for the machine's stability with lifting, moving and lowering items. Telehandler forklifts provide much greater lift heights when compared to a standard forklift. Also called compact telehandlers or high-reach telehandlers, these forklift trucks can lift their full load capacities from 18 feet, for the compact telehandlers, to 56 feet, for the high-reach telehandlers, into the air. Their load capacities usually range between 5,500 and 12,000 pounds. All-wheel steering is popular for all-terrain forklifts and provides increased maneuverability. The power-shift transmission and steering features allow the operator to move the forklift into a safe and successful working proximity. More recently, Telehandler forklift models have included additional features that incorporate the latest in ergonomics. Spacious cabs and tilted steering are some of the items redesigned for the ultimate comfort and productive features. High in demand at job sites, these ergonomic options reduce operator fatigue and repetitive stress injuries. The majority of telehandler forklifts are operated by a single joystick. The joystick is essential for controlling the boom functions and the hydraulics responsible for

forward operation. Telehandler forklifts can also be equipped with non-marking tires which allow them to be used in other applications such as the installation of signs and billboards as well as maintenance on buildings and stadiums. Rotating Telehandler or Roto Telescopic Handler Forklifts Rotating telehandler or roto telescopic handler forklifts have many features in common with the standard telehandler forklift. The rotating telehandler can lift excessive loads to extreme heights safely and efficiently. This unit's added turntable and rotation flexibility increases the types of jobs it can complete. The rotating function allows the forklift to swivel a full 360 degrees around, enabling access a much larger work area without having to reposition the forklift. Commonly, rotating telehandlers have another joystick to handle the rotation portion separately from the lift function. As with the standard telehandler forklift, rotating telehandlers are available with added features including power assist steering, four-wheel drive and minimized slip differential on the rear axle to boost traction and for additional safety. Of course, a machine that can rotate has extra safety considerations to understand. Rotating telehandler rough terrain models come with standard stabilizers to establish more safety while rotating loads back and forth. There are some rotating telehandlers that are designed to move heavy weights without stabilizers to reduce the time it takes to reposition the forklift for work in other areas of the jobsite. Rotator telehandler units are typically smaller than standard telehandlers with their fixed-cab design. Understandably, rotator telehandler machines can handle smaller load capacities compared to their standard telehandler counterparts. Load capacities for rotating telehandlers usually range between 4,000 and 10,000 pounds, with lift heights ranging from 15 to 80 feet. Both telehandlers and rotator telehandlers can be used as a crane when fitted with a winch attachment. This means that these forklifts can sometimes allow a project to forego the need for a crane at the jobsite, saving time, expense and workspace. Advancements for Rough Terrain Forklifts Numerous attachments can be found for rough terrain forklifts including articulating booms, rotating fork carriages, booms, winches and similar items. Forklift attachments are vital for diversifying the machine. They will continue to be developed for years to come. Most of the proposed advancements will consist of included safety features within the rough terrain forklifts. Some new safety features have already been developed such as automatic load restriction devices. These systems automatically weigh a load and then calculate the safe reach distance of that load, taking into consideration the angle and extension of the boom. An alarm will go off once the safe distance is reached. This alerts the operator that immediate adjustments need to be made to the boom angle, reach distance or load weight.